

NEK 2022-13 RFP Questions:

1. There is no separate line on the bid sheet for “traffic control” – is traffic control to be factored into the unit pricing or will it be a ‘pass through’ expense paid by NEK?

Utilization and cost of traffic control will be the responsibility of the contractor. Costs can be factored into the unit pricing or added as a separate line if desired.

2. If traffic control is the burden of the contractor, can the owner or engineer identify the routes that will be built as part of the initial 227 mile project so traffic control can be evaluated – alternately, can the owner/engineer give a percentage of the project that will require traffic control?

The routes to be constructed are depicted on the “Entire Area with and e-911 service levels” map within the RFP. This is a mixture of Federal, State and Municipal roadways, as well as off-road segments. Contractor is to use their discretion as to where traffic control is required and/or desirable.

3. Is there any consideration to altering design to utilize FAP’s instead of MST’s? This could reduce lashing/overlashing expenses and likely ease/eliminate material issues as there are lengthy lead times for MST’s and a broader range of options [and availability] for FAP’s.

The use of MSTs is the owner’s desired design to assure consistency throughout previous, current, and future projects.

4. PM25 units [MST’s] are using a UOM of ‘feet’....will payment be based on the MST factory length or actual footage lashed?

Payment will be made on the actual footage lashed.

5. Are PM 25 units to be single lashed or double lashed?

Units can be single lashed or double lashed at the contractors discretion.

6. BFOV units have a very broad depth range of 24” – 60”, shall we consider this a minimum depth of 24” with contractor discretion to go up to 60” or is it possible that the engineering will require 60” depth on some of these units? A depth of 60” can require additional safety considerations, such as trench boxes, that can add considerably to unit expense.

BFOV should be at a minimum depth of 24". Additional depth will be at contractor discretion or per requirement set by permitting agency.

7. Item CO(AO)10M appears to be strand-only placement [no fiber], why is lashing wire included? Can you please explain this unit?

This unit typically depicts leads that will be served via MST tails and/or long drops.

8. There does not appear to be a designation for adding a tracer wire to any of the buried units – being a dielectric cable, fiber will need tracer wire pulled in for locating purposes, what unit will include that?

Typically, duct placed will have integrated tracer wire.

9. Will an optional flexnap pricing sheet [that better reflects flexnap units] be generated for contractors interested in providing rates?

NEK will explore this. Please indicate your willingness to provide FlexNap pricing and we will follow-up.

10. RFP indicates a requirement to test all fiber before it leaves the warehouse, how does the contractor bill and/or get reimbursed for this?

This requirement is intended to be protection for both NEK and the contractor against manufacturing defects and/or damage incurred in transportation. Cost can be included in your cable unit pricing, or as a separate line item if desired.

11. Will reel testing require every strand or (1) strand per tube for testing.

The extent of this testing is at the contractor discretion; however contractor assumes responsibility for all fiber they deem tests 'good' when taken from the warehouse.

12. What wavelengths are required for reel testing?

Same as above.

13. What is the average reel lengths ordered for this project

Response to follow

14.RFP references installation based on Product and Services specifications, NEK specifications, NRTC specifications, manufacturer recommendations and best industry practices: is there a single project specification reference for this job?

No please refer to RFP sections

15.If there is no project specifications, which entity is the governing entity concerning specifications?

There are project specifications related to the specific material or installation please refer to RFP

16.Where can we find the governing entities specifications, can we receive it electronically?

Specific material related specification will be available

17.What date can we receive project specifications by?

TBD

18.Specifically, what are the specifications for:

- Lashing; dual and/or single

RUS standards

- Testing requirements/methods

Determined by material manufacture and network design

- Tree trimming

TBD based on existing conditions and agreement with NEK

- Bonding/grounding

RUS and Industry standards

- Trenching/boring

TDB

19.RFP indicates that drops/installation are not part of this proposal, why is NID pricing and drop pricing requested?

NEK is seeking only labor pricing for the placement of drops and NIDs as this may be included in future projects.

20.If NID pricing will remain a necessary response, can you please send drawings and specifications for each NID unit type?

See above

21. Is fiber cable armored or unarmored?

Response to follow

22. If fiber cable is armored, please provide any applicable grounding requirements for splicing enclosures

Response to follow

23. If existing anchors have open eyes, will we be permitted to utilize them?

Determined by pole owner as a result

24. Are there any restrictions on workdays and hours?

No restrictions

25. Are there any prevailing wage/Davis Bacon rates associated with this project?

Response to follow

26. Can you detail what a CO(xx) STUB unit is and how it will be utilized in the project?

These are fiber optic cables looped between two enclosures. Utilization is expected to be infrequent.

27. Will drip loops be required under clamps for CO construction?

Drip loops should be utilized per RUS specifications.

28. Can closure be either strapped or lashed at contractors discretion?

RUS specifications

29. Is HAPO (1xSplitter] units for installing the cartridge only and splicing pigtailed to be compensated with HO units?

Response to follow

30. Will OLT cabinets be pole mounted or pad mounted?

Negotiations are currently in progress with property owners. There may be a mixture of pole mounted and pad mounted cabinets.

31. Are as-builts required in a specific electronic format? If so, please indicate requirements.

ESRI Compatible

32. Can the strand used be $\frac{1}{4}$ " 6.6M EHS as opposed to the 5/16(10m) proposed?

10M stand is provided and 10M stand will be the standard